


GM2318S

SOT-23 場效應晶體管(SOT-23 Field Effect Transistors)



N-Channel Enhancement-Mode MOS FETs

N 溝道增強型 MOS 場效應管

■MAXIMUM RATINGS 最大額定值

Characteristic 特性參數	Symbol 符號	Rat 額定值	Unit 單位
Drain-Source Voltage 漏極-源極電壓	BV_{DSS}	40	V
Gate- Source Voltage 柵極-源極電壓	V_{GS}	± 20	V
Drain Current (continuous) 漏極電流 - 連續	I_D	4	A
Drain Current (pulsed) 漏極電流 - 脉冲	I_{DM}	16	A
Total Device Dissipation 總耗散功率 $T_A=25^\circ\text{C}$ 環境溫度為 25°C	P_D	1040	mW
Junction 結溫	T_J	150	$^\circ\text{C}$
Storage Temperature 儲存溫度	T_{stg}	-55 to +150	$^\circ\text{C}$

■DEVICE MARKING 打標

GM2318S=C18S



GM2318S

■ELECTRICAL CHARACTERISTICS 電特性

($T_A=25^\circ\text{C}$ unless otherwise noted 如無特殊說明，溫度為 25°C)

Characteristic 特性參數	Symbol 符號	Min 最小值	Typ 典型值	Max 最大值	Unit 單位
Drain-Source Breakdown Voltage 漏極-源極擊穿電壓($I_D=250\mu\text{A}$, $V_{GS}=0\text{V}$)	BV_{DSS}	40	—	—	V
Gate Threshold Voltage 柵極開啓電壓($I_D = 250\mu\text{A}$, $V_{GS} = V_{DS}$)	$V_{GS(\text{th})}$	1	—	3	V
Diode Forward Voltage Drop 內附二極管正向壓降($I_S=1\text{A}$, $V_{GS}=0\text{V}$)	V_{SD}	—	0.8	1.2	V
Zero Gate Voltage Drain Current 零柵壓漏極電流($V_{GS}=0\text{V}$, $V_{DS}=40\text{V}$)	I_{DSS}	—	—	1	μA
Gate Body Leakage 柵極漏電流($V_{GS}=\pm20\text{V}$, $V_{DS}=0\text{V}$)	I_{GSS}	—	—	±100	nA
Static Drain-Source On-State Resistance 静态漏源導通電阻($I_D=4\text{A}$, $V_{GS}=10\text{V}$)	$R_{DS(\text{ON})}$	—	32	40	$\text{m}\Omega$
Static Drain-Source On-State Resistance 静态漏源導通電阻($I_D=3.5\text{A}$, $V_{GS}=4.5\text{V}$)	$R_{DS(\text{ON})}$	—	50	65	$\text{m}\Omega$
Input Capacitance 輸入電容 ($V_{GS}=0\text{V}$, $V_{DS}=20\text{V}$, $f=1\text{MHz}$)	C_{ISS}	—	560	—	pF
Output Capacitance 輸出電容 ($V_{GS}=0\text{V}$, $V_{DS}=20\text{V}$, $f=1\text{MHz}$)	C_{OSS}	—	70	—	pF
Gate Charge 柵極電荷密度 ($V_{DS}=15\text{V}$, $V_{GS}=10\text{V}$, $I_D=2\text{A}$)	Q_g	—	5	—	nC
Turn-ON Time 开啓時間 ($V_{DS}=20\text{V}$, $V_{GS}=10\text{V}$, $R_{GEN}=1\Omega$)	$t_{(\text{on})}$	—	12	—	ns
Turn-OFF Time 短斷時間 ($V_{DS}=20\text{V}$, $V_{GS}=10\text{V}$, $R_{GEN}=1\Omega$)	$t_{(\text{off})}$	—	37	—	ns

Pulse Width $\leq 300 \mu\text{s}$; Duty Cycle $\leq 2.0\%$

GM2318S

■TYPICAL CHARACTERISTIC CURVE

典型特性曲线




Figure 1: Output Characteristics




Figure 2: On-Resistance vs. Junction Temperature




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Gate-Source Voltage




Figure 5: Gate-Charge Characteristics




Figure 6: Safe Operating Area