


GM2333

SOT-23 場效應晶體管(SOT-23 Field Effect Transistors)



P-Channel Enhancement-Mode MOS FETs

P 溝道增強型 MOS 場效應管

■MAXIMUM RATINGS 最大額定值

Characteristic 特性參數	Symbol 符號	Rat 額定值	Unit 單位
Drain-Source Voltage 漏極-源極電壓	BV_{DSS}	-12	V
Gate- Source Voltage 柵極-源極電壓	V_{GS}	± 8	V
Drain Current (continuous) 漏極電流-連續	I_D	-5.1	A
Drain Current (pulsed) 漏極電流-脉沖	I_{DM}	-20	A
Total Device Dissipation 總耗散功率 $T_A=25^\circ\text{C}$ 環境溫度為 25°C	P_D	1250	mW
Junction 結溫	T_J	150	$^\circ\text{C}$
Storage Temperature 儲存溫度	T_{stg}	-55 to +150	$^\circ\text{C}$

■DEVICE MARKING 打標

GM2333=2333



GM2333

■ELECTRICAL CHARACTERISTICS 電特性

(T_A=25°C unless otherwise noted 如無特殊說明，溫度為 25°C)

Characteristic 特性參數	Symbol 符號	Min 最小值	Typ 典型值	Max 最大值	Unit 單位
Drain-Source Breakdown Voltage 漏極-源極擊穿電壓(I _D = -250uA, V _{GS} =0V)	BVDSS	-12	—	—	V
Gate Threshold Voltage 柵極開啓電壓(I _D = -250uA, V _{GS} = V _{DS})	V _{GS(th)}	-0.4	—	-1	V
Diode Forward Voltage Drop 內附二極管正向壓降(I _S = -1A, V _{GS} =0V)	V _{SD}	—	—	-1.2	V
Zero Gate Voltage Drain Current 零柵壓漏極電流(V _{GS} =0V, V _{DS} = -12V)	I _{DSS}	—	—	-1	uA
Gate Body Leakage 柵極漏電流(V _{GS} =±8V, V _{DS} =0V)	I _{GSS}	—	—	±100	nA
Static Drain-Source On-State Resistance 靜態漏源導通電阻(I _D = -5.1A, V _{GS} = -4.5V)	R _{DS(ON)}	—	28	35	mΩ
Static Drain-Source On-State Resistance 靜態漏源導通電阻(I _D = -4.5A, V _{GS} = -2.5V)	R _{DS(ON)}	—	38	45	mΩ
Static Drain-Source On-State Resistance 靜態漏源導通電阻(I _D = -2A, V _{GS} = -1.8V)	R _{DS(ON)}	—	50	59	mΩ
Input Capacitance 輸入電容 (V _{GS} =0V, V _{DS} = -10V, f=1MHz)	C _{ISS}	—	920	—	pF
Output Capacitance 輸出電容 (V _{GS} =0V, V _{DS} = -10V, f=1MHz)	C _{OSS}	—	220	—	pF
Turn-ON Time 开啓時間 (V _{DS} = -10V, I _D = -2A, R _{GEN} =6Ω)	t _(on)	—	8	—	ns
Turn-OFF Time 矩斷時間 (V _{DS} = -10V, I _D = -2A, R _{GEN} =6Ω)	t _(off)	—	60	—	ns

Pulse Width≤300 μ s; Duty Cycle≤2.0%