


GMN5030

SOT-23 場效應晶體管(SOT-23 Field Effect Transistors)



N-Channel Enhancement-Mode MOS FETs

N 溝道增強型 MOS 場效應管

■MAXIMUM RATINGS 最大額定值

Characteristic 特性參數	Symbol 符號	Rat 額定值	Unit 單位
Drain-Source Voltage 漏極-源極電壓	BV_{DSS}	500	V
Gate- Source Voltage 柵極-源極電壓	V_{GS}	± 30	V
Drain Current (continuous) 漏極電流 - 連續	I_D	300	mA
Drain Current (pulsed) 漏極電流 - 脉冲	I_{DM}	2	A
Total Device Dissipation 總耗散功率 TA=25°C 環境溫度為 25°C	P_D	900	mW
Junction 結溫	T_J	150	°C
Storage Temperature 儲存溫度	T_{stg}	-55 to +150	°C

■DEVICE MARKING 打標

GMN5030=J30



GMN5030

■ELECTRICAL CHARACTERISTICS 電特性

($T_A=25^\circ\text{C}$ unless otherwise noted 如無特殊說明，溫度為 25°C)

Characteristic 特性參數	Symbol 符號	Min 最小值	Typ 典型值	Max 最大值	Unit 單位
Drain-Source Breakdown Voltage 漏極-源極擊穿電壓($I_D = 250\mu\text{A}$, $V_{GS} = 0\text{V}$)	BV_{DSS}	500	—	—	V
Gate Threshold Voltage 柵極開啓電壓($I_D = 250\mu\text{A}$, $V_{GS} = V_{DS}$)	$V_{GS(\text{th})}$	2.5	—	3.8	V
Diode Forward Voltage Drop 內附二極管正向壓降($I_S = 2\text{A}$, $V_{GS} = 0\text{V}$)	V_{SD}	—	—	1.2	V
Zero Gate Voltage Drain Current 零柵壓漏極電流($V_{GS} = 0\text{V}$, $V_{DS} = 500\text{V}$)	I_{DSS}	—	—	1	μA
Gate Body Leakage 柵極漏電流($V_{GS} = \pm 30\text{V}$, $V_{DS} = 0\text{V}$)	I_{GSS}	—	—	± 100	nA
Static Drain-Source On-State Resistance 靜態漏源導通電阻($I_D = 0.4\text{A}$, $V_{GS} = 10\text{V}$)	$R_{DS(\text{ON})}$	—	10	13	Ω
Input Capacitance 輸入電容 ($V_{GS} = 0\text{V}$, $V_{DS} = 400\text{V}$, $f = 1\text{MHz}$)	C_{ISS}	—	120	—	pF
Output Capacitance 輸出電容 ($V_{GS} = 0\text{V}$, $V_{DS} = 400\text{V}$, $f = 1\text{MHz}$)	C_{OSS}	—	20	—	pF
Turn-ON Time 开啓時間 ($V_{DS} = 300\text{V}$, $I_D = 0.2\text{A}$, $R_{GEN} = 6\Omega$)	$t_{(\text{on})}$	—	6	—	ns
Turn-OFF Time 短斷時間 ($V_{DS} = 300\text{V}$, $I_D = 0.2\text{A}$, $R_{GEN} = 6\Omega$)	$t_{(\text{off})}$	—	8	—	ns

Pulse Width $\leq 300 \mu\text{s}$; Duty Cycle $\leq 2.0\%$